



All wood and pellet appliances featured in this publication are EPA certified under 2.5 g/h or EPA exempt.



Wood Stoves

www.drolet.ca

Clearances and options description on back page

Blackcomb II

DB02811



↕ MEDIUM

OPTIONS: 1, 3, 4, 5, 6, 7

Columbia II

DB03016



↕ MEDIUM

OPTIONS: 1, 3, 4, 5, 6, 7

Savannah II

DB03028



↕ MEDIUM

OPTIONS: 1, 3, 4, 5, 6, 7

Escape 1500

DB03135



↕ MEDIUM

OPTIONS: 1, 3, 4, 5, 6, 7

Deco II

DB03205



↕ MEDIUM

OPTIONS: 1, 3, 4, 5, 6, 7

Escape 1800

DB03102



↕ LARGE

OPTIONS: 2, 3, 4, 5, 6, 7

Austral III

DB03033



↕ X-LARGE

OPTIONS: 1, 3, 4, 5, 6, 7

Black Stag II

DB03411



↕ X-LARGE

OPTIONS: 1, 3, 4, 5, 6, 7

Myriad III

DB03052



↕ X-LARGE

OPTIONS: 3, 4, 5, 6, 7

Blower included

Legend III

DB03073



↕ X-LARGE

OPTIONS: 3, 4, 5, 6, 7

Blower included

Escape 2100

DB03129



↕ X-LARGE

OPTIONS: 1, 3, 4, 5, 6, 7

HT-3000

DB07300



↕ X-LARGE

OPTIONS: 1, 3, 4, 5, 6, 7

Drolet wood stoves general features (see clearances on back page)

	Blackcomb II	Columbia II	Savannah II	Escape 1500	Deco II	Escape 1800	Austral III	Black Stag II	Myriad III	Legend III	Escape 2100	HT-3000
Heating area	1,800 ft ²	1,800 ft ²	1,800 ft ²	1,800 ft ²	1,800 ft ²	2,100 ft ²	2,300 ft ²	2,300 ft ²	2,300 ft ²	2,300 ft ²	2,700 ft ²	2,700 ft ²
BTU/h maximum	65,000	65,000	65,000	65,000	65,000	75,000	90,000	90,000	90,000	90,000	110,000	110,000
Efficiency	78%	78%	78%	78%	78%	77%	78%	78%	78%	78%	77%	77%
Dimensions W x D x H	24 7/8" (632 mm) 23 5/8" (600 mm) 30 5/8" (778 mm)	25 5/8" (651 mm) 25 1/8" (638 mm) 29" (737 mm)	24 7/8" (632 mm) 23 5/8" (600 mm) 30 5/8" (778 mm)	24 7/8" (632 mm) 24 1/2" (622 mm) 29 7/8" (759 mm)	23 7/8" (600 mm) 23" (584 mm) 36 5/8" (930 mm)	25 5/8" (651 mm) 26 3/4" (679 mm) 32 5/8" (829 mm)	23 3/4" (603 mm) 32 1/2" (826 mm) 32 1/8" (816 mm)	24 1/4" (616 mm) 32 1/4" (819 mm) 32 3/4" (832 mm)	24 1/4" (603 mm) 32 1/8" (816 mm) 34 3/8" (873 mm)	24 1/4" (616 mm) 32 3/8" (822 mm) 32 5/8" (829 mm)	28 1/8" (714 mm) 31 7/8" (810 mm) 34 1/2" (876 mm)	28 1/8" (714 mm) 31 1/4" (794 mm) 36 3/8" (925 mm)
Particulate emissions rate	1.26 g/h	1.26 g/h	1.26 g/h	1.26 g/h	1.26 g/h	1.54 g/h	0.95 g/h	0.95 g/h	0.95 g/h	0.95 g/h	1.32 g/h	1.32 g/h
Log length	18" (457 mm)	18" (457 mm)	18" (457 mm)	18" (457 mm)	18" (457 mm)	20" (508 mm)	20" (508 mm)	20" (508 mm)	20" (508 mm)	20" (508 mm)	22" (559 mm)	22" (559 mm)
Flue pipe diameter	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)	6" (152 mm)
Ash pan	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Wood Burning Cook Stoves (EPA exempt)

Wood Inserts

Outback Chef

DB04800

↕ MEDIUM

MADE IN ITALY



Atlas

DB04810

↕ MEDIUM

MADE IN SPAIN



Escape 1500-I

DB03137



↕ MEDIUM

Blower included
Faceplate included

OPTIONS: 4, 5, 6, 7, 18

TRIO

1X Escape 1500-I Wood insert
1X Faceplate **
1X VOLKI-625 Flex liner kit

Also available

TRIO

ITEMS INCLUDED:



Escape 1800-I

DB03125



↕ LARGE

Blower included
Faceplate kit must be ordered separately.

OPTIONS: 5, 6, 18, 19, 20, 21

TRIO

1X Escape 1800-I Wood insert
1X AC03370 Faceplate
1X VOLKI-625 Flex liner kit

Drolet wood burning cook stoves general features

	Outback Chef	Atlas
Firebox volume	1.08 ft ³	1.91 ft ³
Oven dimensions W x D x H	11 1/2" x 17 3/4" x 11 3/4" 289 mm x 450 mm x 298 mm	21 1/2" x 13" x 8 3/4" 546 mm x 330 mm x 222 mm
Dimensions W x D x H	40" x 25 7/8" x 33 5/8" 1016 mm x 657 mm x 854mm	27" x 18" x 49 3/8" 686 mm x 457 mm x 1254 mm
Thermometer on oven	Yes	Yes
Log length	16" (406 mm)	15-18" (381-457 mm)
Shipping Weight	545 lb (248 kg)	330 lb (150 kg)

*See the clearances table in the owner's manual for each appliance on www.drolet.ca

Drolet wood inserts general features

	Escape 1500-I	Escape 1800-I
Heating area	1,800 ft ²	2,100 ft ²
BTU/h maximum	65,000	75,000
Efficiency	78%	77%
Dimensions W x D x H	27 1/4" X 22 3/8" X 21 1/4" 692 mm x 568 mm x 540 mm	28 3/8" X 26 3/8" X 23 1/8" 721 mm x 670 mm x 587 mm
Particulate emissions rate	1.26 g/h	1.54 g/h
Log length	18" (559mm)	20" (508 mm)
Flue pipe diameter	6" (152 mm)	

‡ Faceplate kit must be ordered separately. **Faceplate Included with the appliance



All wood and pellet appliances featured in this publication are EPA certified under 2.5 g/h or EPA exempt.



Pellet Stoves

Gas Wall Mounted Room Heater

Eco-55DP00070

⬆️ MEDIUM

Eco-55 STD00071

⬆️ MEDIUM

🏠

🚚

OPTIONS: 8, 9, 10, 11, 12, 13, 14, 15, 16

Drolet wood burning pellet stoves general features		
	Eco-55	Eco-55 ST
Heating area	2,000 ft²	
BTU/h maximum	39 260 BTU/h	
Efficiency	78.4%	
Loading capacity	60 lb (27 kg)	80 lb (36 kg)
Combustion autonomy (on low)	51 h	69 h
Dimensions W x D x H	25 1/8" x 29 1/2" 32 5/8" 638 mm x 749 mm x 829 mm	25 1/8" x 29 1/2" x 36 1/8" 638 mm x 749 mm x 918 mm
Feeding system	Top-feed	
Flue pipe diameter	3"	
Heat settings	6	
Electronic ignition	Yes	
Thermostatic or manual mode	Yes	
Ash pan	Yes	
Clearances*		
Sides	6" (152 mm)	
Back	3" (76 mm)	
Corners	3" (76 mm)	

*These clearances are also valid for an alcove installation.

Clearances for Drolet wood stoves*						
	SINGLE WALL PIPE			DOUBLE WALL PIPE		
	BACK	SIDES	CORNERS	BACK	SIDES	CORNERS
Blackcomb II	14 1/2" (368 mm)	10" (254 mm)	12" (305 mm)	7-1/2" (191 mm)	10" (254 mm)	12" (305 mm)
Columbia II	14 1/2" (368 mm)	10" (254 mm)	12" (254 mm)	7-1/2" (191 mm)	10" (254 mm)	12" (305 mm)
Savannah II	14 1/2" (368 mm)	16" (406 mm)	12" (305 mm)	7-1/2" (191 mm)	16" (406 mm)	12" (305 mm)
Escape 1500	14 1/2" (368 mm)	10" (254 mm)	12" (305 mm)	6" (152 mm)	10" (254 mm)	12" (305 mm)
Deco II	14 1/2" (368 mm)	16" (406 mm)	12" (305 mm)	7-1/2" (191 mm)	16" (406 mm)	12" (305 mm)
Escape 1800	15" (381 mm)	17" (432 mm)	10" (254 mm)	6" (152 mm)	17" (432 mm)	7" (127 mm)
Austral III	14 1/2" (368 mm)	20" (508 mm)	12" (305 mm)	7-1/2" (191 mm)	20" (508 mm)	10" (254 mm)
Black Stag II	14 1/2" (368 mm)	20" (508 mm)	12" (305 mm)	7-1/2" (191 mm)	20" (508 mm)	10" (254 mm)
Myriad III	14 1/2" (368 mm)	20" (508 mm)	12" (305 mm)	7-1/2" (191 mm)	20" (508 mm)	10" (254 mm)
Legend III	14 1/2" (368 mm)	12" (305 mm)	10" (254 mm)	7-1/2" (191 mm)	12" (305 mm)	8" (203 mm)
Escape 2100	13" (330 mm)	14" (356 mm)	7-1/4" (184 mm)	6" (152 mm)	14" (355 mm)	7" (178 mm)
HT-3000	13" (330 mm)	14" (356 mm)	7-1/4" (184 mm)	6" (152 mm)	14" (355 mm)	7" (178 mm)

DV45DG04905K

NEW!

Stainless steel venting system
Premium quality blower (130 CFM) and conversion kit (LP-NG) included.

Gas wall mounted room heater general features	
	DV45
Fuel type	Propane or natural gas
Electrical requirement	120V / 60Hz
Gas inlet diameter	1/2" NPT
Ignition type	Manual
Pilot type	Continuous pilot
Maximum input	13,750 BTU (4.03 kW)
Minimum input	7,536 BTU (2.21 kW)
Turn down capacity	45%
Type of chimney	Direct vent
Vent dimension	3.14" x 5.11"
Recommended heating area	150 - 500 pi²
Overall dimension (W x D x H)	32 3/8" x 8 7/8" x 24 3/4"
USA standard (emissions)	ANSI Z21 86-2016
Tested and listed as per applicable standards	By an accredited laboratory (CAN/USA)
Warranty	Limited 5 years

Clearances	
Sides	6" (152 mm)
Back	6" (152 mm)
Corners	6" (152 mm)

	Escape 1500-I	Escape 1800-I
A Adjacent sidewall	16" (406 mm)	
B Combustible side surround	9" (229 mm)	9" (229 mm)
C Combustible top surround	27" (686 mm)	27" (686 mm)
D Combustible mantel shelf	27" (686 mm)	27" (686 mm)
E Minimum floor protection in front of unit	16" (406 mm)	
F Minimum masonry opening (W x D x H)	27 1/2" (700 mm) 12 3/4" (324 mm) 21 1/2" (546 mm)	28 7/8" (733 mm) 15 3/4" (400 mm) 23 3/8" (594 mm)

*See the clearances table on the owner's manual for each appliance on www.drolet.ca

Visit our Facebook page and discover every month offers you cannot miss !

Get a manufacturer's mail-in rebate or a free selected product with the purchase of a wood or pellet heating appliance.

OPTIONS

1

VARIABLE SPEED BLOWER
AC02050

2

VARIABLE SPEED BLOWER
AC03095

3

QUICK CONNECT THERMIDISC KIT
AC02055

4

FIRESCREEN
AC01281 (FITS ON ESCAPE 2100, HT-3000)
AC01299 (FITS ON ESCAPE 1500 STOVE AND INSERT, DECO II, COLUMBIA II, SAVANNAH II)
AC01315 (FITS ON ESCAPE 1800)
AC01397 (AUSTRAL III, BLACK STAG II, LEGEND III, MYRIAD III)

5

5" FRESH AIR INTAKE REGISTER WITH AIRTIGHT DAMPER
AC01349

6

FRESH AIR INTAKE KIT
AC01204 (BLACK STAG II, AUSTRAL III, LEGEND III)
AC01291 (COLUMBIA II)
AC01298 (ESCAPE 1500 INSERT)
AC01315 (ESCAPE 1800 INSERT)
AC01334 (DECO II)
AC01336 (ESCAPE 1500, HT-3000, ESCAPE 2100, BLACKCOMB II, MYRIAD III, SAVANNAH II)

7

5" DIAMETER INSULATED PIPE, 4' LENGTH
AC02090

8

DIGITAL WALL MOUNTED THERMOSTAT
AC05558

9

FRESH AIR INTAKE KIT FOR PELLET STOVES
3" DIAMETER, 5' LENGTH AC01240
4" DIAMETER, 5' LENGTH AC01239

10

3" DIAMETER INSULATED FLEX PIPE FOR FRESH AIR INTAKE KIT, 10' LENGTH
AC02092

11

55 SERIES HOPPER EXTENSION
AC01393

12

ON-OFF THERMOSTATIC REMOTE CONTROL
AC02012

13

PROGRAMMABLE THERMOSTATIC REMOTE CONTROL
AC05568

14

3" GROUND FLOOR VENTING KIT FOR PELLET STOVES
VOPKGF03

15

4" GROUND FLOOR VENTING KIT FOR PELLET STOVES
VOPKGF04

16

4" BASEMENT VENTING KIT FOR PELLET STOVES
VOPKB04

17

25' FLEX LINER KIT, 6" DIAMETER
VOLKI-625
35' FLEX LINER KIT, 6" DIAMETER
VOLKI-635

18

6" LINER OFFSET ADAPTOR FOR WOOD INSERT
AC01370

19

REGULAR FACEPLATE FOR ESCAPE 1800-I
29" (737 MM) X 44" (1118 MM)
AC03370

20

LARGE FACEPLATE FOR ESCAPE 1800-I
32" (813 MM) X 50" (1270 MM)
AC03375

21

CUTTABLE FACEPLATE FOR ESCAPE 1800-I 32" (813 MM) X 50" (1270 MM)
AC01357

MOBILE HOME
APPROVED APPLIANCE

APPLIANCE CAN
BE INSTALLED IN
ALCOVE

HPBA
Hearth, Patio & Barbecue Association

Technical data contained in this sale sheet are for reference only. Any installation must be done according to the data and drawings detailed in the Owner's manual, consult: www.drolet.ca.

Safety tested and verified according to USA Standards by an accredited laboratory.

Some changes may have been made to the products after the publication of this page. SBI reserves itself the right to modify its products without any obligation on its part.
Technical data contained in this sale sheet are for reference only. Any installation must be done according to the data and drawings detailed in the Owner's manual, consult: www.drolet.ca.

250, RUE DE COPENHAGUE, SAINT-AUGUSTIN-DE-DESMAURES, (QUÉBEC) CANADA G3A 2H3

PUB038

7 73388 99509 0

06-2020 PRINTED IN CANADA